

GALP FORMULA PLUS 5W40

Fully synthetic lubricant for gasoline or diesel passenger cars engines. It improves engine performance, optimizes fuel consumption and protects the engine effectively.

Properties

- Anti-rust and anti-oxidation protection at high and low temperatures.
- Excellent lubricating film stability which maintains all its properties even under extreme pressure and temperature conditions.
- Reinforced detergent / dispersant capabilities, ensuring that engines remain perfectly clean by inhibiting the accumulation of soot.
- Its low content in phosphorus helps catalyst converters function more efficiently and last longer and reduces emissions levels, thus making a positive contribution to environmental protection.
- High fluidity at low temperatures ensuring that a protective lubricant film covers all engine components immediately after starting.

Specifications/ Approvals

ACEA A3/B4
API SN/CF
VW 502.00/ 505.00
MB APPROVAL 229.3

Main Features

(typical values)

SAE Grade	5W-40
Density at 15°C, kg / l (D1298)	0,86
Viscosity index (D2270)	172
Kinematic viscosity at 40°C, mm ² /s (D445)	85
Kinematic viscosity at 100°C, mm ² /s (D445)	14,1
Pour point, °C (D97)	- 39
Flash point, °C (D92)	230

Available packaging

Drum, 205 L
Box, 4x5 L
Box, 18x1 L



FPC 904 – JUL15
R&D – LUB - GPA

Help protect the environment: do not dispose of used oils by dumping them in drainage systems, waterways or on the ground.
GL.15003a