

GALP GALAXIA LD STAR

Multigrade lubricant, formulated based on highly refined minerals, recommended for diesel engines of heavy cargo and passenger transport vehicles subject to very severe driving and running conditions. This oil was especially developed for modern vehicles demanding lubricants complying with standards **ACEA E7, API CI-4** and **Volvo VDS-3**.

Properties

- Highly stable lubricating film whose viscosity properties remain practically unaltered during the lubricant's lifetime. The oil's properties ensure very long oil change intervals;
- Greater detergent / dispersant capabilities for a perfectly clean engine by preventing carbon deposits;
- Excellent anti-wear protection;
- Easy cold starting due to its good fluidity at low temperatures.

Specifications/ Approvals

ACEA	E7/E5
API	CI-4/SL
MB	APPROVAL 228.3
MAN	M3275
VOLVO	VDS-3
RENAULT	RVI RLD/RLD-2
DAF	HP-2
MACK	EO-N
CAT	ECF-2, ECF-1a
GLOBAL	DHD-1
CUMMINS	CES 20071/72/76/77/78
MTU	TYPE 2
ZF	TE-ML 07C/04C
KOMATSU	EO15W40-DH

Main Features

(typical values)

SAE Grade	15W-40
Density at 15°C, Kg / l (D1298/D4052)	0,884
Viscosity index (D2270)	138
Kinematic viscosity at 40°C, mm ² /s (D445)	106
Kinematic viscosity at 100°C, mm ² /s (D445)	14,3
Pour point, °C (D97), max.	- 27
Flash point, °C (D92)	226
TBN (Total Base Number), mg KOH/g (D2896)	9,4

Available Packaging

IBC 1000 L
Drum 205 L
Pail 20 L
Box, 4 x 5 L
Bulk



FPC 607 - R4 - SEP15
R&D - LUB - GPA

Help protect the environment: do not dispose of used oils by dumping them in drainage systems, waterways or on the ground.
GL.15003a